US ERA ARCHIVE DOCUMENT

# Development of a Quantitative Accounting Framework for Black Carbon and Brown Carbon from Emissions Inventory to Impacts

Jamie Schauer, UW-Madison (PI)
Mike Bergin, Georgia Teach (Co-PI)
Collaborator: Jerry Liu, Cummins







#### Motivation

- Emissions inventories and air quality models of light adsorbing carbon require parameterization of the radiative properties of emissions
- Current parameterizations of light absorbing carbon emissions do not address the range of variability within sources or control technologies
- Elemental carbon is not a good surrogate for light absorbing carbon for control strategy development nor assessment of control strategy implementation
  - May be OK if limited to absorption at 880 nm
- The light absorbing capacity of carbonaceous aerosol is not a conservative property from the point of emissions to atmosphere





#### **Project Goals**

#### Overall Goal

 Development of a quantitative framework for sourcereceptor relationships for light absorbing carbon and their associated wavelength dependent light absorptivity

#### Key Objectives

- Deconstruct emissions from sources of light absorbing carbon to elucidate the contribution of different emissions components to wavelength dependent absorption
- Elucidate how the evolution of emissions in plumes impact wavelength dependent absorption
- Integrate source apportionment models for aerosol components impacting light adsorption with wavelength dependent light absorption closure calculations





#### **Project Strategy**

- Source Testing
- Mie theory calculations for source emissions and deconstructed emissions
- Atmospheric measurements
- Mie theory calculations for atmospheric aerosols and deconstructed aerosols
- Develop a source apportionment framework that can address the optical evolution of aerosols and precursors





#### Source Testing

- Examine key sources of light absorbing carbon:
  - Mobile sources
    - Conventional CI and SI and Emerging Technologies
  - Biomass burning
    - Lab and Field Studies
  - Coal combustion
- Examine for each source
  - Role of process variables on emissions
  - Optical properties of the organic carbon
  - Optical properties of the elemental carbon
  - Impact of dilution
  - Impact of thermal stripping of organics
- Develop source specific light absorption closure models for measurement conditions and high dilution conditions



#### Atmospheric Measurements

- Use sites where we have conducted source apportionment studies in the past and where historical record and optical measurements
  - Atlanta, Georgia
    - Near Roadway
  - Rural Alabama
    - SOA
  - India
    - Biomass and Trash Burning
    - Low Temperature Coal Combustion






#### Approach

- Measure the optical properties under controlled conditions
  - Scattering and Absorption (multiple wavelengths)
- Measure physical-chemical properties
  - Size distribution, particle shape, chemical composition
- Segregate components of aerosols
  - Thermal Denuder, WS and Organic solvent atomization
- Correct absorption artifacts and compare optical properties of aerosol components






#### Methods








Magee Scientific AE31 7-channel Aethalometer





TSI Scanning Mobility Particle Sizer/ Electrostatic classifier

DMT PAX 532: Photoacoustic Extictionometer



Framework for Black Carbon and Brown Carbon from Emissions to Impacts EPA STAR Grant R83503901


#### Methods













Framework for Black Carbon and Brown Carbon from Emissions to Impacts EPA STAR Grant R83503901


#### Attenuation by Non-Absorbing Aerosols





#### Absorption vs Scattering: Scattering Artifact correction


				slope forced through	
Wavelengths	slope (m)	Intercept (b)	R^2	zero (m')	
370	0.064	3.977	0.801747	0.066	
470	0.049	-0.909	0.816126	0.048	
520	0.038	1.983	0.835205	0.039	
590	0.030	2.919	0.801001	0.032	
660	0.027	3.207	0.84761	0.028	
880	0.016	7.607	0.685092	0.019	
950	0.013	7.410	0.651662	0.016	








#### Multiple Wavelength Absorption Correction







- Test run at steady-state
- Scattering correction is not significant for engine out emissions
- Loading correction is wavelength specific



#### **Example of Wood Pellets**










Framework for Black Carbon and Brown Carbon from Emissions to Impacts EPA STAR Grant R83503901






#### **Experimental Setup**

Model	2010, Cummins ISX15 – 500	
Emission Certification	EPA 2010, CARB 2010	
Туре	4-stroke cycle	
Cylinder Configuration	In-line 6	
Bore and Stroke	137 mm x 169 mm	
Compression Ratio	17.2:1	
Aspiration	Turbocharged & Charge Air	
	Cooled	
Displacement	14.9 L	
Rated Power & Rated Speed	373 kW & 1800 RPM	
Peak Torque	2508 N-m at 1200 RPM	
Fuel System	Cummins XPI	
EGR System	Cooled High Pressure	









#### **Emissions Testing Lab**











#### **BrC Plots**









# Atmospheric Sampling: Objectives

- Conduct field measurements at a variety of sites dominated by various sources of Black Carbon (BC) and Brown Carbon (BrC)
- Determine relative fraction of light absorption by BC and BrC
- Determine sources of BC and BrC
- Develop simple parameterizations for influence of aging on the light absorbing properties of aerosols






#### **Approach: Specifics**


Parameter	Instrument	Dates	Objective
Real-Time			•
Continuous			
σ <sub>ap</sub> (λ)	Magee Aethalometer, PAX	4-1 Month Periods	Compare with Mie Theory Light Absorption Estimates from MOUDI 1
$\sigma_{\sf sp}$ ( $\lambda$ )	Radiance Research Nephelometer		Compare with Mie Theory Estimates from MOUD
Time-Integrated Sampling			
EC/OC, Trace Organics, WSOC, Abs $(\lambda)_{solvent}$ , Abs $(\lambda)_{water}$	HiVol Filter sampler	4-1 Month Periods	Source apportionment, RI Estimates for Mie Theory, Solvents Extracts for Aerosolization Experiments
EC/OC, WSOC, Abs $(\lambda)_{solvent}$ , Abs $(\lambda)_{water}$	MOUDI 1	4-1 Month Periods	Estimation of $\sigma_{\text{ap}}$ ( $\lambda$ ) as function of size for both water and solvent extracts and BC
Mass, Ions	MOUDI 2	4-1 Month Periods	Estimation of $\sigma_{\text{sp}}$ ( $\lambda$ ) as a function of size





#### Black Carbon (BC) and Angstrom Absorption Exponent (AAE) in rural US and India









# Trash/Refuse Burning: A Source of Brown Carbon











## Ratio of light absorption for denuder (200°C) to ambient air







### Ratio of light absorption for denuder (200°C) to ambient air










#### Low Cost Sensor Networks

microAet h-Black Carbon Arduinomicrocontroler



PM sensor

CO<sub>2</sub> Sensor

T, RH


npacts



Framework for Blac

EPA STAR Grant R83503901

# Atlanta Freeway PM Emission Factor Estimate




**Rush Hour Event** 

Rough Emissions Factor =  $\Delta PM/\Delta CO2$ = 0.079µg m<sup>-3</sup> PM/ppmCO2 = 0.39 g PM/kg fuel





# Atlanta Freeway BC Emission Factor Estimate



Rough Emissions Factor =  $\Delta BC/\Delta CO2$ = 0.044 µg m<sup>-3</sup> BC/ppmCO2 = 75 mg BC/kg fuel





#### **Ongoing Efforts**

- Source Testing
  - Appling methodology to other source of concern: real world biomass, residential coal
- Atmospheric Sampling
  - Water and methanol extractions of size-resolved
     BC and BrC samples
  - Extraction of hivol samples to determine optical properties and sources of light absorption
- Publications



